



Athira plywood USA Inc  
1000 Northbrook Drive ,  
Suite,100  
Trevose , PA , 19053  
845-405-6399  
[Joe@Athiraplywood.com](mailto:Joe@Athiraplywood.com)  
[www.athiraplywoodusa.com](http://www.athiraplywoodusa.com)

## Indonesian White Birch Plywood Specifications

Veneer Cut	R/C, WPF
Size	48"x 96" , 48.5"x96.5"
Thickness	19MM,18MM,15MM,12MM,9MM,5.2MM
Grade	B2,C2,D2
Core	Falcata+Jabon
Calibration	-.5/+ .2
Moisture	<12%
Origin	Indonesia
Certification	CARB Phase 2 , TSCA TITLE VI
Finish	Raw & Pre Finished
Glue Type	Interior, TSCA TITLE VI, CARB
Face Veneer Thickness	0.3mm
Sanding	240 Grit Finish



### Indonesian White Birch Plywood Features

- ❖ Lighter core.
- ❖ Very high nailing and screwing strength.
- ❖ High Bonding strength -No Delamination.
- ❖ 100 %Calibrated
- ❖ Thickness tolerance as per international plywood standards (IWPA,HPVA).
- ❖ Maintains Perfect structure , No warping issues.
- ❖ No Core gaps -100% composed cores
- ❖ 100% Machine dried core used
- ❖ Ideal for application were weight is Important
- ❖ Perfect .5 Calibration

Thickness	No of Plies	Sheet/Crate	Weight/Sheet
5.2	5	180	14 Lbs
9	5	100	26 Lbs
12	7	75	34 Lbs
18	9	50	52 Lbs
19	9	50	54 Lbs

Applications: Furniture, Cabinetry, TrimWork, Fixtures, Closets, Lamination,General Woodworking etc.