

Athira plywood USA Inc 1000 Northbrook Drive , Suite,100

Trevose, PA, 19053 845-405-6399

Joe@Athiraplywood.com www.athiraplywoodusa.com

## FSC Certified - Marine Grade Plywood - BS 6566

Marine-grade plywood is a hardwood plywood bonded with exterior-grade adhesive and manufactured to meet British Standards 6566. It is a durable, high-strength plywood with very minimal voids, making it ideal for marine applications with the less expensive option to BS1088

Veneer Cut	R/C, WPF		
Size	48"x 96",48.5"x96.5"		
Thickness	21MM,18MM,15MM,12MM,9MM,6MM,4MM		
Grade	BS 6566 B / BB		
Core	100 % Meranti		
Calibration	+/3		
Moisture	<10%		
Origin	Malaysia		
Certification	CARB Phase 2 , TSCA TITLE VI		
Finish	Raw		
Glue Type	Exterior -WBP		
Face Veneer Thickness	Red Meranti 1.2 MM		
Sanding	240 Grit Finish		

Thickness	No of Plies	Sheet/Crate	Weight/Sheet
4	3	175	22 Lbs
6	5	140	32 Lbs
9	5	95	50 Lbs
12	7	70	64 Lbs
15	9	58	70 Lbs
18	11	48	78 Lbs
21	13	45	85 Lbs

## FSC Certified -Marine Grade Plywood - BS 6566 Features

- Uniform, Light Red Meranti face and core veneers.
- Very high nailing and screwing strength.
- ❖ High Bonding strength -No Delamination.
- Thickness tolerance as per international plywood standards (IWPA,HPVA).
- Maintains Perfect structure, No warping issues.
- Very Minimal Core voids
- ❖ Flat & smooth Surface for laminating
- ❖ Exterior Glue for High moisture environments
- Veneers have a uniform grain pattern, and the boards can be sanded smoothly on both sides
- ❖ Perfect for CNC machining applications



Athira plywood USA Inc 1000 Northbrook Drive , Suite,100

Trevose , PA , 19053 845-405-6399

Joe@Athiraplywood.com www.athiraplywoodusa.com